

Product availability : Stock - Normally stocked in distribution facility



Price\* : 372.00 USD



## Main

Product or component type	Industrial Control Transformer
Power Rating	250 VA
Primary Voltage	240 x 480 V 230 x 460 V 220 x 440 V
Secondary Voltage	120/240 V 115/230 V 110/220 V
Type	T

## Complementary

Phase	1 phase
Power Rating	250 VA per UL 250 VA per CSA 250 VA per NOM 160 VA per CE
Primary to Secondary Voltage	220 x 440 V : 110/220 V 230 x 460 V : 115/230 V 240 x 480 V : 120/240 V
Temperature rise	80 °C
Electrical connection	Screw clamp terminals
Height	3.2 in
Width	3.75 in
Depth	5.3 in
Material	Copper winding
Fingersafe Cover Compatibility	FSC2

## Environment


Product certifications	CE UL listed file E61239
------------------------	-----------------------------

Enclosure Type	Not rated (open device)
Insulation temperature	266 °F (130 °C)

### Ordering and shipping details

Category	16201 - 9070 T (NOT TF) 250-2000VA
Discount Schedule	CP8
GTIN	00785901845584
Nbr. of units in pkg.	1
Package weight(Lbs)	7.9800000000000004
Returnability	Y
Country of origin	MX

### Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant  <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations
California proposition 65	WARNING: This product can expose you to chemicals including:
- - - - - Substance 1	Phenyl glycidyl ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm.
- - - - - More information	For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>

### Contractual warranty

Warranty period	10 years
-----------------	----------